

Task Factory Amazon


Last Modified on 20 January 2022

🔔 Task Factory users running version 2020.1.4 or older (released prior to May 27, 2020): **There's an important Task Factory update.** Please visit [here](#) for more details.

AmazonS3 Rest Connection Manager

Connection Properties

Used with the AmazonS3 Rest [Source](#) and AmazonS3 Rest [Destination](#).



AmazonS3 Rest Connection Manager

Connection Properties

Proxy Configuration

Access Key ID:


Access Key:

Test Connection OK Cancel

| Option | Description |
|---------------|--|
| Access Key ID | The Access Key ID provided by Amazon Web Services to connect to the desired container. |
| Access Key | The Access Key provided by Amazon Web Services. |

Note: **Test Connection** requires the IAM user to have *ListAllMyBuckets* permissions. To find the available permissions for your IAM user, [open the AWS Console](#), select the user and look under **Permission Policies**. You may need to add/edit the policy to add *ListAllMyBuckets* permissions.


Proxy Configuration



| Option | Description |
|------------------------|---|
| Proxy Host | Identifies the proxy address. |
| Proxy Port | Identifies the port used by the proxy. |
| Proxy User Name | Enter the user name for proxies that require user authentication. |
| Proxy Password | Enter the password for proxies that require user authentication. |

AmazonS3 Rest Source

Source




Begin by creating a connection manager that connects to the service's storage container.

Format

The following formats are available:

Delimited Format

Users can manually configure the delimiter, quote identifiers, the lines to skip, and lines to scan. Select **Detect Formats** to configure these fields automatically.



| Option | Description |
|-----------------------|---|
| Delimiter | Identifies the character that separates columns. The default value is the comma (,). |
| Quote | Identifies the character used to indicate a value (if present). |
| Lines To Skip | Users can designate the number of lines to skip at the beginning of the delimited file. |
| Auto | Automatically detects which lines to skip. |
| Lines To Scan | Determines the number of lines to scan when detecting the file. |
| Detect Formats | Select this button to begin scanning the chosen file. |

Detected Delimited View - After the format is detected, a new view appears that allows users to configure or change different properties of the file.

Json Format

TF Amazon S3 Rest Source

Amazon S3 Source allows a connection to Amazon S3 for storage services

Source

Format

Output Columns

Error Handling

Preview

Format: **Json**

Root JSON Path

Columns

| Column Name | Token Path | Data Type | Length | Precision | Scale | Code Page |
|-------------|------------|-----------|--------|-----------|-------|-----------|
| | | | | | | |

Add New Output Column Remove Output Column

Date Parse Handling: None

Date Time Zone Handling: Local


Float Parse Handling: Double

OK Cancel Help

| Option | Description |
|----------------------------|---|
| Root Json Path | JSON queries can return multiple levels, therefore, this field identifies the root to be used. |
| Output Columns | In this window, users can add and remove columns, define their name, token path (defined within the raw data), data type, length, precision, scale, and code page. |
| Date Parse Handling | Specifies how date formatted strings are parsed when reading JSON text. <ul style="list-style-type: none"> • None - Strings are not parsed as a date type and are read as strings. • DateTime - Date formatted strings are parsed as DateTime. • DateTime Offset - Date formatted strings are parsed as DateTimeOffset. |
| | Specifies how to treat time values converted between string and DateTime. <ul style="list-style-type: none"> • Local - Treats the time as local (UTC times convert to local times.) • Utc - Treats the time as UTC. This converts local time to UTC. |

| | |
|--------------------------------|---|
| Date Time Zone Handling | <ul style="list-style-type: none"> • Unspecified - Treats the time as local time if a DateTime is being converted to a string. If a string is being converted to DateTime, convert to a local time if a time zone is specified. • RoundtripKind - Time zone is preserved when converting. |
| Float Parse Handling | <p>Specifies how floating point numbers are parsed.</p> <ul style="list-style-type: none"> • Double - Floating point numbers are parsed as a double datatype. • Decimal - Floating point numbers are parsed as a decimal datatype. |

XML Format



| Option | Description |
|-------------------------|--|
| Root XPath Query | <p>Xml queries can return multiple levels, therefore, this field identifies the root to be used.</p> |
| | |

| | |
|---------------------------|---|
| Option Namespaces: | <ul style="list-style-type: none"> • Prefix - Identifies the prefix used in an XML namespace. Example: In the element \ the prefix is url. • Uri - The url or address identified in the namespace. |
| Columns | Users can create, remove, and configure the name, index (zero-based), data type, length, precision, and scale of the columns being extracted from the file. |

Output Columns

Users can select which columns to include/exclude in the output. Additionally, users can rename the columns by selecting into its corresponding output name.

TF Amazon S3 Rest Source


TF Amazon S3 Rest Source

Amazon S3 Source allows a connection to Amazon S3 for storage services

| Source | Include | Name | Output Name |
|-----------------------|-------------------------------------|-------------------|--------------|
| Format | <input checked="" type="checkbox"/> | BusinessEntityID | ID |
| Output Columns | <input checked="" type="checkbox"/> | FirstName | FirstName |
| Error Handling | <input checked="" type="checkbox"/> | LastName | LastName |
| Preview | <input checked="" type="checkbox"/> | AddressLine1 | AddressLine1 |
| | <input checked="" type="checkbox"/> | AddressLine2 | AddressLine2 |
| | <input checked="" type="checkbox"/> | City | City |
| | <input checked="" type="checkbox"/> | StateProvinceCode | State |
| | <input checked="" type="checkbox"/> | PostalCode | ZipCode |
| | <input checked="" type="checkbox"/> | PhoneNumber | ContactPhone |

OK Cancel Help


Error Handling



| Option | Description |
|-----------------------|--|
| Not Used | Error handling is not used and no error constraint is available. |
| Ignore Failure | All errors are ignored and the package continues to execute. |
| Redirect Row | All error rows are directed to an error output. |
| Fail Component | (Default selection) On error, the component fails and the package execution stops. |

Preview


Select **Preview Data** after configuring the previous tabs to view an output sample.



AmazonS3 Rest Destination


Target

Begin by creating a connection manager that connects to an Amazon Storage container. After a connection manager is created, the source window populates with files and folders. Select the desired file to continue configuration.




| Option | Description |
|-------------------------|--|
| Target Item Name | Defines the name and extension of the file you would like to create when the component is executed. For example: MyNewXmlList.xml |

Delimited Format




| Option | Description |
|---------------------------|---|
| Delimiter | Identifies the character that separates text. |
| Quote | Identifies the character (single or double quote) that indicates value. |
| Include Header Row | Writes the column headers at the beginning of the document. |
| Encoding | Selects which encoding is used to create the document. |
| Culture | Used to identify the document's language culture. |

Json Array Format



| Option | Description |
|-----------------|---|
| Generate | Select to automatically generate the Row Body metadata. Users can also add custom header and footer data. |
| Encoding | Select which encoding is used to create the document. |
| Culture | Used to identify the document's language culture. |

XML Array Format



| Option | Description |
|-----------------|---|
| Generate | Select to automatically generate the Row Body metadata. (Users can also add custom header and footer data.) |
| Encoding | Select which encoding is used to create the document. |
| Culture | Used to identify the document's language culture. |